



		5
		6
		7
2.1		8
2.2		9
2.2.1		9
2.2.2		9
2.2.3		11
		12
3.1		12
3.2		12
3.3		13
		14
4.1		14
4.2		14
4.3		14
		15
5.1		15
5.2		
5.2.1		16
5.2.2	/	16
5.2.3		
5.2.4		17
5.2.5		17
5.3		
5.3.1	/	
5.3.2		19
5.3.3		19
5.3.4		19
5.3.5		20
		2

5.3.6				 	 	 	20
5.3.7				 	 	 	21
5.3.8				 	 	 	22
5.3.9				 	 	 	24
5.3.10				 	 	 	24
5.3.11				 	 	 	25
5.3.12				 	 	 	25
5.3.13	CSV			 	 	 	26
5.3.14		/	/	 	 	 	26
5.4				 	 	 	27
5.4.1				 	 	 	27
5.4.2				 	 	 	28
5.4.3				 	 	 	
5.4.5				 	 	 	
5.4.6				 	 	 	
.4.7				 	 	 	
5.5				 	 	 	
5.5.1				 	 	 	
5.5.2				 	 	 	
5.5.3				 	 	 	
5.5.4				 	 	 	
5.5.5				 	 	 	
5.5.6				 	 	 	
5.6				 	 	 	
5.7				 	 	 	
6.1				 	 	 	
6.2				 	 	 	
				 	 	 	40
7.1				 	 	 	40
7.2				 	 	 	41
1				 	 	 	42



/

1.1		
1.1.1		UPS
1.1.2		
1.1.3		
1.1.4		
1.1.5		
1.1.6	0.5-2.5mm	
1.1.7		
1.1.8		

1.2		
1.2.1		
1.2.2		
1.2.3		
1.2.4	(5.2.3)
1.2.5		
1.2.6		
1.2.7		

1.2.8



















7 x2





x2

x2











2.2.1



2.2.2













А.

HP TIJ2.5		
(H*W*D):151*93*3	2mm 175*52*33mm	
3 16mm	350 280mm	
30V/3A, 90W		
1-12.7mm		
(DPI)	(m/min)	
600	30.4	
400	45.7	
300	60.9	
150	121.9	
	/	
/		
1.		
2. USB1		
3. USB2 U 4 DB15		
5.20		
5inch 800*480	LCD	
1.		
2. HP		
3.		
 CE FCC		
1+	10%-85%RH	
2 ·	+ 80 10%-90%RH	

В.

 Arial	
UPCA UPCE EAN13 EAN8 INT25 CODE39	
CODE128 EAN128 PDF417 DATAMATRIX QR	

C.

1. HP TIJ2.5 42ml 370ml 350ml

2.



1		2.3	
2			
3	-	5.1	
4	-	<mark>粤</mark> ▶ 开启	
5			
6		<mark>疊∎ 停止</mark>	InkJet
7			

1	
2	0.5- 2.5mm
3	
4	
5	

1	
2	



, 1)	(4 4 4		读 料	e iz W	X IR	 ▲ ↓ ↓
		(5.2)	/				
			/	,			(5.3)	
0 设置		(5.4)					
*		(5.5)					
					USE	3			
				5.7					

/



5.2.2 /



5.2.3



5.2.4



5.2.5

点击	; 2



5.3.1 /



A: Default; 2 Default	
В 12-156	
1-12.7mm	
C. 1-300%	
D. 78	
E. X 0 Y 0 F 0.90.180	
G.	
	🔒 资料名称MSG002 📰 🛩 返回





Α.	·····································		
			18
В.			
		19	
C.			
	20 21		10



Α.	
В.	
USB	
S1P1	
S1PN	
SN PN	
SGPN:	

5.3.10





5.3.13 CSV



5.3.14 / /





ô	设置	📰 📥 🎦 🏞 🗮
	○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○○	※ ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●
1)		



5.4.3





5.4.6











5.5.1









5.5.4



5.5.5

	🗙 14 💿 🏶 🖁 🔞 🙆
	COD Technology
LOGO	較件版本2.3 0.6437 硬件版末16.52.3F 设备作为明6000012 客户编码;145受误称。→

5.5.6

\land		
[6] 重重		
	48	
		49
49		40
		10
		49
1		
2		n+1 n Default
1		
2		
3		4
4		mm
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		5
17		30m/min
18	DPI	300DPI

	50	51	52	53	
A.	50				
				50	C
В.	51				
				51	1
C.	52			52	

D.

	1) 2)
	1)	
	2)	10%
	3)	
USB	U	SB
		U

6.1		
6.1.1		
6.1.2		
6.1.3		
0.5-2.5mm	(
6.1.4		
6.1.5		
6.1.6		
6.1.7		
6.1.8		

)

- 1.
- 2.

		A. 6.2	
1	1.	B. 5.4.3	1.
			2.
	2.		
2		Α.	
2		В.	
		F 7	
3	1.	5.7	
	1.		1.
4	2.		2. 3. ISM 4. ISM

1		1.	A. AC DC B.	
		2.		
		3.		
		1.		
		2.		
		3.		
2		4.		
		5.	5.7	
		6.	5.2.2	S
		7.		Ø

1		30mm
		30mm
2		9
		9
3		1min
		10
		09
4		10 2:01
		10
		11
5		
6		
7		
8		
9		